

LIFTING SLINGS

Meuwissen Gerritsen's lifting slings are manufactured from 100% polyester and comply with the stipulated NEN 1492-1 standard and EC Machinery Directive version 2006/42/EC. The polyester lifting slings are fully recyclable and thus also meet the highest environmental standards. In addition, all lifting straps include instructions for use on the label.

Application

Lifting slings are indispensable for safely lifting window frames and facade, floor and roof elements. This allows products to be safely transported internally and externally. The lifting slings can be easily processed due to the flexible sling fabric and are available in various lengths and lifting loads.

Ranafita

- ✓ Available in different lengths and lifting loads
- ✓ Flexible to process
- ✓ 100% recyclable
- ✓ Highly resistant to alkaline influences
- ✓ Optional printing with text or company name
- ✓ Provided with a certificate

Description	WLL*	Thickness	Operating length	Width	Safety factor	Colour	Article no.	Quantity per box
MG Lifting sling	300 kg	2,2 mm	0,30 m	25 mm	SF 7:1	White	9303003000	1000 pcs
	300 kg	2,2 mm	$0,40\mathrm{m}$	25 mm	SF 7:1	White	9303004000	750 pcs
	500 kg	2,2 mm	1,00 m	25 mm	SF 7:1	Blue	9305010000	250 pcs
	750 kg	2,2 mm	1,00 m	30 mm	SF 7:1	Orange	9307510000	250 pcs
	1000 kg	2,2 mm	1,00 m	30 mm	SF 7:1	Purple	9310010000	125 pcs

^{*} Check the safe working load table on the next page to make sure you hoist safely.











SAFE WORKING LOAD TABLE

	Vertical	Strapped	Parallel ±7°	ß = 0-45°	ß = 45-60°
Article no.					
9303003000 / 9303004000	300 KG	240 KG	600 KG	420 KG	300 KG
9305010000	500 KG	400 KG	1000 KG	700 KG	500 KG
9307510000	750 KG	600 KG	1500 KG	1050 KG	750 KG
9310010000	1000 KG	800 KG	2000 KG	1400 KG	1000 KG



