



**PERFO®**

**Perfo® is a micro perforated transparent LPDE membrane reinforced with polypropylene fabric.**

**Application**

Perfo® is used in facades as a breathable layer on the outside (cold side) in facades. Perfo® is also used as a temporary glazing liner for wind and watertighting facade openings during construction. The microperforation allows construction moisture to drain to the outside.

**Benefits**

- ✓ Watershed
- ✓ Breathable
- ✓ Suitable as temporary glazing

Description	Width	Length	Article no.	EAN code	Quantity	Weight
Perfo®	1,50 m 3,00 m	50 m 50 m	6209015020 6209030020	8714672002324 8714672002539	26 roll / pallet 26 roll / pallet	7 kg 14 kg




Facade



Breathable



Waterproof



Resistant up to 80 °C



Maximum 3 months UV-resistant

**Specifications**

Open construction phase <b>3 months</b>	Temperature resistance <b>- 20 °C / 70 °C</b>
Weight <b>90 gr / m<sup>2</sup></b>	Water vapour resistance <b>Sd 0,3 m</b>
Nail tear resistance initial (length) <b>165 N</b>	Water tightness <b>W2</b>
Nail tear resistance initial (cross) <b>170 N</b>	Fire class <b>F</b>
Tensile strength initially (length) <b>175 N / 50 mm</b>	Elongation at break (length) <b>12 %</b>
Tensile strength initially (cross) <b>125 N / 50 mm</b>	Elongation at break (cross) <b>14 %</b>
Water vapour transmission <b>80 g / m<sup>2</sup> / day</b>	





**PERFO®**

### Installation

Perfo® is micro-perforated, which means that it has limited waterproofing and should therefore be processed free of hard substrates. In facades with a soft substrate, for example mineral wool, the Perfo® may be applied directly to the soft substrate. Apply the Perfo® in a shingle fashion. For horizontal overlaps, maintain a minimum of 100 mm and a maximum of 200 mm. Apply the Perfo® to the structure using stainless steel staples with maximum spacing of 150 mm. Tape off staples and seams with VASTR® membrane tape basic.

### Associated products

**Tyvek®**

FlexWrap tape



**MG VASTR®**

Membrane tape basic



**MG VASTR®**

Butyl tape



**MG VASTR®**

Nail Sealing tape



#### Description

Tyvek® FlexWrap tape

VASTR® Membrane tape basic

VASTR® Butyl tape

VASTR® Nail Sealing tape

#### Width

60 mm

75 mm

30 mm

60 mm

#### Length

10 m

25 m

20 m

20 m

#### Article no.

8106001000

8107502501

8103002000

8106002010

#### EAN code

5450208029771

8714672002621

8714672005233

8714672005332

#### Quantity

3 roll / box

20 roll / box

8 roll / box

5 roll / box



### Membrane guide

Do you need advice on which membrane to use for your project?

Find the most suitable product in just one minute with our membrane guide. Scan the QR code with the camera of your smartphone and find out which product you need.

*All our products are intended exclusively as building or construction materials. Therefore, the user of our products is expected to be familiar with the basic principles of building physics, the regionally applicable building standards and the official national building regulations. Meuwissen Gerritsen B.V. and/or our employees are not liable for any damage resulting from (careless or incorrect) use of our products.*



MEUWISSEN GERRITSEN

INFO@MG-BOUW.COM

023 - 303 28 08

MG-BOUW.COM