

MG MIOFOL®

PE Film ECO

The Miofol® PE film Eco is an LDPE (Low Density Poly Ethylene) membrane and has been specially developed for use in the carpentry and prefabrication industry. Due to the use of special raw materials and ideal dimensions, the PE film Eco is most commonly used as a vapour control membrane for roof and facade elements. This is because in the conditioned conditions of precast productions, reinforced membrane is less necessary. Miofol® PE film Eco is available as standard in thicknesses of 0.15 and 0.20mm. The Eco variant is made of regenerate; recycled polyethylene.

Application

The Miofol® PE film Eco is used on the warm side of wall and roof constructions. Due to its constant vapour control property, the membrane is suitable in constructions of buildings belonging to climate class 2 and 3, such as homes, offices, schools, etc. PE film Eco protects the construction against moisture and provides optimal airtight insulation.

Benefits

- ✓ Vapourproof
- ✓ Air & watertight
- ✓ Roll widths on element width
- ✓ High tensile strength and elongation at break
- ✓ Processing faster than folded membrane
- ✓ Recyclable

Description	Width	Length	Article no.	EAN code	Quantity	Weight
PE Film Eco	0,15 mm	2,60 m	100 m	4201526001	8714672002027	33 roll / pallet
	0,15 mm	2,60 m	50 m	4201526000	8714672002010	59 roll / pallet
	0,15 mm	3,00 m	100 m	4201530001	8714672002041	52 roll / pallet
	0,15 mm	3,00 m	50 m	4201530000	8714672002034	52 roll / pallet
	0,20 mm	2,60 m	100 m	4202026001	8714672002058	22 roll / pallet
	0,20 mm	2,60 m	50 m	4202026000	8714672002065	46 roll / pallet
	0,20 mm	3,00 m	100 m	4202030001	8714672002089	21 roll / pallet
	0,20 mm	3,00 m	50 m	4202030000	8714672002072	39 roll / pallet

CUSTOM PE MEMBRANE

The Miofol® PE film is completely customizable. Are you looking for a different roll size or thickness? Contact us for the possibilities!

