

MG MIOFOL®

PE FILM PRO

The Miofol® PE film Pro is an LDPE (Low Density Poly Ethylene) membrane and is specifically designed for use in the carpentry and prefabrication industry. Due to the use of special raw materials and ideal dimensions, the PE Vapour control membrane Pro is most commonly used as a vapour control membrane for roof and facade elements. This is because in the conditioned conditions of precast productions, reinforced membrane is less necessary. The Miofol® PE film Pro is available as standard in thicknesses of 0.15 and 0.20mm (true thickness). The Pro variety is made of a clean, clear grade of polyethylene.

Application

The Miofol® PE membrane Pro is used on the warm side of wall and roof constructions. Due to its constant vapour control property, the membrane is suitable in constructions of buildings belonging to climate class 2 and 3, such as homes, offices, schools, etc. PE film Pro protects the construction against moisture and provides optimal airtight insulation.

Benefits

- ✓ Vapourproof
- ✓ Air & watertight
- ✓ Guaranteed true thickness
- ✓ Roll widths on element width
- ✓ High tensile strength and elongation at break
- ✓ Processing faster than folded membrane
- ✓ Recyclable

Description	Width	Length	Article no.	EAN code	Quantity	Weight
PE Film Pro	0,15 mm	2,60 m	100 m	2201526001	8714672002096	28 roll / pallet
	0,15 mm	2,60 m	50 m	2201526000	8714672002102	59 roll / pallet
	0,15 mm	3,00 m	100 m	2201530001	8714672002119	28 roll / pallet
	0,15 mm	3,00 m	50 m	2201530000	8714672002126	52 roll / pallet
	0,20 mm	2,60 m	50 m	2202026000	8714672002133	46 roll / pallet
	0,20 mm	3,00 m	100 m	2202030001	8714672002140	18 roll / pallet
	0,20 mm	3,00 m	50 m	2202030000	8714672002157	39 roll / pallet

CUSTOM PE MEMBRANE

The Miofol® PE film is completely customizable. Are you looking for a different roll size or thickness? Contact us for the possibilities!

