

# MG MIOFOL®

## VS2

**Miofol® VS 2 is a 3-layer floor membrane, including 3 mm PE foam and a blue HDPE top layer. Miofol® VS 2 features an overflap and an integrated adhesive strip. This extremely vapour barrier floor membrane also has a leveling and sound-reducing function.**

### Application

Miofol® VS 2 is specially developed for floating laid laminate and parquet floors. It levels minor unevenness in the substrate and reduces impact sound. Due to the overlap with integrated adhesive strip as well as the HDPE top layer, the Miofol® VS 2 has an extreme vapour barrier capability. It is often applied double as an anti-friction layer (sliding membrane) under seamless concrete screeds for ice rinks, as for example in the Thialf and Sochi.

### Benefits

- ✓ Reduces flanking sound transmission
- ✓ Prevents cracks in finish floors due to action in the structural floor
- ✓ Features an integrated adhesive strip and membrane flap
- ✓ Easy to process
- ✓ Suitable for cement screeds and anhydrite screeds
- ✓ Extremely vapour retardant
- ✓ CFC- and HCFC-free
- ✓ High tear and puncture resistance

Description	Width	Length	Article no.	EAN code	Quantity	Weight
Miofol® VS2	1,50 m	35 m	3227015000	8714672000436	10 roll / pallet	12 kg



Floor



For wooden floors



Waterproof



Vapour barrier



Protected against masonry mortar

### Specifications

Water vapour resistance <b>Sd &gt; 150 m</b>	Temperature resistance <b>-20 °C / 70 °C</b>
Weight <b>225 gr / m²</b>	Water vapour transmission <b>&gt; 0,15 gr / m² / day</b>
Nail tear resistance initial (length) <b>95 N</b>	Water tightness <b>W1</b>
Nail tear resistance initial (cross) <b>95 N</b>	Fire class <b>F</b>
Tensile strength(length) <b>205 N / 50 mm</b>	Elongation at break (length) <b>114 %</b>
Tensile strength(cross) <b>105 N / 50 mm</b>	Elongation at break(cross) <b>62 %</b>
R-Value <b>0,11 m² K / W</b>	Noise reduction <b>+ / - 4 dB</b>



# MG MIOFOL®

## VS2

### Installation

Roll out Miofol® VS 2 on a flat and clean swept floor and set it up against the walls. Using the integrated adhesive strip and overlap, join the sheets together to form a closed moisture barrier and cut off the excess at the walls after one hour. When used as an anti-friction layer, Miofol® VS 2 is used double, with the blue HDPE top layers processed against each other.



### Related products

#### Tyvek®

FlexWrap tape



#### MG VASTR®

Membrane tape basic



#### MG VASTR®

Butyl tape



#### MG VASTR®

Total tape



### Description

Tyvek® FlexWrap tape

### Width

60 mm

### Length

10 m

### Article no.

8106001000

### EAN code

5450208029771

### Quantity

3 roll / box

VASTR® Membrane tape basic

75 mm

25 m

8107502501

8714672002621

20 roll / box

VASTR® Butyl tape

30 mm

20 m

8103002000

8714672005233

8 roll / box

VASTR® Total tape (black)

60 mm

25 m

8106002502

8714672000474

10 roll / box

VASTR® Tota tape (black)

100 mm

25 m

8110002501

8714672000481

6 roll / box

VASTR® Totaal tape (white)


60 mm

25 m

8106002501

8714672999884

10 roll / box



### Membrane guide

Do you need advice on which membrane to use for your project?

Find the most suitable product in just one minute with our membrane guide. Scan the QR code with the camera of your smartphone and find out which product you need.

*All our products are intended exclusively as building or construction materials. Therefore, the user of our products is expected to be familiar with the basic principles of building physics, the regionally applicable building standards and the official national building regulations. Meuwissen Gerritsen B.V. and/or our employees are not liable for any damage resulting from (careless or incorrect) use of our products.*



MEUWISSEN GERRITSEN

INFO@MG-BOUW.COM

023 - 303 28 08

MG-BOUW.COM