

Tyvek® TAPE



Tyvek® tape is a one-sided HDPE tape coated with a thick layer of water-based modified acrylic adhesive and a siliconized paper release liner. Excellent resistance to time, water, moisture, the weather elements and chemicals. Tyvek® tape can be used for sealing membranes and is particularly suitable for repairing damage to Tyvek® Roofliner, Tyvek® Firecurb™ Housewrap and Polytex® Pro.

Application

Tyvek® tape should be applied for wind and watertight sealing of Tyvek® membranes in facade or roof structures. Both the durable repair of damage, wind and watertight sealing of overlap seams or staples, and the connection of Tyvek® membranes to structures should be processed with Tyvek® tape. Tyvek® tape can be adhered directly to wooden or steel substrates.

Installation

Tyvek® tape must be applied to a dust and grease-free, dry surface to ensure proper adhesion. Before applying Tyvek® tape, remove the release liner and apply the tape to the center of the seam / overlap. Press and rub the tape well to eliminate air bubbles and provide optimum permanent adhesion.

Description	Width	Quantity	Article no.	EAN code
Tyvek® tape	50 mm x 25 m	12 roll / box	8105102500	5450208027549
Tyvek® tape	60 mm x 25 m	10 roll / box	8106102500	5450208027562
Tyvek® tape	75 mm x 25 m	8 roll / box	8107502500	8714672003710
Tyvek® tape plus	60 mm x 25 m	10 roll / box	8106302500	5450208029481
Tyvek® tape Speedliner 12/48	60 mm x 25 m	10 roll / box	8106202500	5450208027685
Tyvek® tape Speedliner 50/50	100 mm x 25 m	6 roll / box	8110002500	5450208027623

Specifications

Color White with blue printing	Adhesion to steel 25N / 25 mm
Material HDPE	
Adhesive layer Modified acrylic	Protective coating Release liner
Temperature resistance -40 °C to +100 °C	Processing temperature From 0 °C
Storage Dark, dry, 10 °C to 20 °C	

