MG VASTR® SEAL PRO

VASTR® Seal Pro is an extremely adhesive and double-sided sealing tape. VASTR® Seal Pro has very high initial and permanent adhesion to all substrates. VASTR® Seal Pro is particularly suitable for bonding membranes on uneven substrates.

Application

VASTR® Seal Pro should be used when airtight bonding membranes against an uneven substrate such as a masonry wall. VASTR® Seal Pro acts like an assembly adhesive but without the curing time. VASTR® Seal Pro adheres immediately and provides a completely sealed bond of the membrane to a connecting surface.

Installation

VASTR® Seal Pro must be applied to a dust and grease free, dry surface to ensure good adhesion. Apply VASTR® Seal Pro and press firmly. Remove the release paper and press the membrane firmly into the tape. Rub down so that air bubbles disappear and an optimum durable bond is created.

 Description
 Size
 Quantity
 Article no.
 EAN code

 VASTR® Seal Pro
 10 mm x 12 m
 10 roll / box
 8101001200
 8714672999945

Specifications

Color Adhesion to steel
Transparent >25 N / 25 mm

Material **Dispersion adhesive based on polyacrylate**

Storage

Dry, -5 °C to 10 °C

Protective coating Release liner

Adhesive layer **Dispersion adhesive based on polyacrylate**

Temperature resistance -30 °C to +80 °C

Processing temperature From 0 °C



