



VASTR® Total tape is a single-sided adhesive tape and is universally applicable for membranes and air sealing of the building envelope. The tape in black or white versions features a VASTR® high performance adhesive layer. The top layer of the tape is UV resistant for two years which makes this tape suitable for both indoor and outdoor applications.

Application

VASTR® Total tape can be used as a universal tape to provide an airtight finish to the building envelope. Thereby, the VASTR® Total tape adheres to many common substrates. Masking overlaps in membranes (non-woven or PE), repairing tears, masking of board material or insulation are all among applications to make a construction airtight. VASTR® Total tape is universally applicable to all our membranes from Alkreflex®, Miofol®, Polytex® and TAFTEX®.

Installation

VASTR® Total tape must be applied to a dust and grease free, dry surface to ensure good adhesion. Before applying VASTR® Total tape, remove the release liner and apply the tape to the center of the seam / overlap. Press and rub the tape well to eliminate air bubbles and provide optimum permanent adhesion. For optimal adhesion, a primer should be used on absorbent substrates.

Description	Size	Color	Quantity	Article no.	EAN code
VASTR® Total tape	60 mm x 25 m	Black	10 roll / box	8106002502	8714672000474
	100 mm x 25 m	Black	6 roll / box	8110002501	8714672000481
	60 mm x 25 m	White	10 roll / box	8106002501	8714672999884

Specifications

Color White & Black	Adhesion to steel >25 N / 25 mm
Material LDPE membrane with reinforcement	
Adhesive layer Acrylic copolymer	Protective coating Release liner
Storage Dark, dry, 10 °C to 23 °C	
Temperature resistance -30 °C to 100 °C	Processing temperature From 0 °C

